


ELECTRICAL CHARACTERISTICS	
CENTER FREQUENCY(f_0)	1880,1960 MHz
3 dB PASSBAND	$f_0(*)\pm 40$ dB
PASSBAND INSERTION LOSS	<2 dB
PASSBAND RETURN LOSS	<14 dB
50 dB REJECTION	$f_0(*)\pm 117.5$ MHz
OPERATING TEMP.	-40 TO +85°C

COPY

Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.



NOTES:
 FOR RECOMMENDED FOOTPRINT SEE FP0014.
 RECOMMENDED ATTACHMENT METHOD: SILVER EPOXY OR REFLOW NOT TO EXCEED AS INDICATED BELOW:
 TEMP.(°C) MAX.TIME(SEC)

215	90
230	60
245	30
260	15

ENGLISH / METRIC ENGLISH	CHECKED BY					
TOLERANCES UNLESS OTHERWISE SPECIFIED MACHINED SURFACES TO BE 125 OR BETTER REMOVE ALL BURRS	DRAWN BY RME ENGINEER SWB	II	15JUN01	SWB	DEV.	INI. ISS. PER 1650
ENGLISH (INCHES) .XX ±.02 .X ±.05 .XXX ±.010	SCALE 2:1	REV	DATE	BY	DCN No.	REMARKS
METRIC (MM) .X ±.25 .XX ±.13	DATE 19JUN01	APPLIC: CERAMIC COAXIAL FILTER				
ANGLES ± 0° 30'	FINISH: BOARD: NI/AU PLATED COPPER JACKET: NI/SILVER RESONATOR: SILVER	TITLE: 5BCR6B-fo(*)/80-L				
	DRAWING No. 0L0337	SHEET NO/OF 1 1				