


**COPY**

ELECTRICAL CHARACTERISTICS			
CENTER FREQUENCY:	898.5 MHz NOM	937.5 MHz NOM	
PASSBAND:	896-901 MHz	935-940 MHz	
60 dBc REJECTION:	935-940 MHz	896-901 MHz	
PASSBAND LOSS:	<4.5 dB	<4.5 dB	
PASSBAND VSWR:	<1.7:1	<1.7:1	
(S23) ISOLATION (850-1000 MHz):	>55 dBa		



Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.

NOTES:  
 HAND OR WAVE SOLDERING.  
 MAX REFLOW TEMP. 240°C FOR 30 SEC. OR 260°C FOR 15 SEC.

FILTER IS ROHS COMPLIANT.  
 FILTER MAY BE ETCHED OR LABELED.

ENGLISH / METRIC ENGLISH	CHECKED BY				
TOLERANCES UNLESS OTHERWISE SPECIFIED MACHINED SURFACES TO BE 125 / OR BETTER REMOVE ALL BURRS	DRAWN BY PBF				
ENGLISH (INCHES) .XX ±.02 .XXX ±.01	METRIC (MM) .X ±.25 .XX ±.13	SCALE 2:1	DATE 07MAY07	APPLIC: CERAMIC COAXIAL FILTER	TITLE: 9DCR6E-898.5/937.5/15-D
ANGLES ± 0° 30'	FINISH: PIN: TIN PLATED JACKET: NI/SILVER RESONATOR: SILVER	DRAWING No. 0L0722	SHEET/OF 1 / 1		

