



Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.

NOTES:

RECOMMENDED ATTACHMENT METHOD: SILVER EPOXY OR REFLOW NOT TO EXCEED AS INDICATED BELOW:

TEMP.(°C) MAX.	TIME(SEC)
215	90
230	60
245	30
260	15

FILTER MAY BE LABELED OR ETCHED.
FILTER IS ROHS COMPLIANT.

ENGLISH / METRIC		CHECKED BY					
ENGLISH		DRAWN BY					
TOLERANCES UNLESS OTHERWISE SPECIFIED		PBF					
MACHINED SURFACES TO BE 125 / OR BETTER		ENGINEER		II	08APR08	KJR	DEV.
REMOVE ALL BURRS		KJR		REV	DATE	BY	DCN No.
REMARKS		INI. ISS. PER 2865					
ENGLISH (INCHES)		SCALE		APPLIC:			
METRIC (MM)		4:1		CHIP AND WIRE FILTER			
.XX ±.02		DATE		TITLE:			
.XXX ±.010		14APR08		7LLC1-400-L			
ANGLES ± 0° 30'		FINISH:		BOARD: NI/GOLD		DRAWING No.	
				JACKET: NI/SILVER		0L0867	
						SHEET OF	
						1 1	